



组件 - 塑料  
UL 档案号: E525617

HENAN CINOWIN NEW MATERIALS CO LTD

1 Northeast Corner Of The Intersection Of Baoquan Road And Meihua Avenuebaoshan Economic Technological Development Zone  
Hebi, HENAN 458000 China



PA DG7455

Polyamide 66 (PA66), pellets

可燃性	值	测试方法
UL 阻燃等级		
0.8 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
0.8 mm, ALL	HB75	IEC 60695-11-10, -20
电气性能	值	测试方法
热丝引燃 (HWI)		UL 746A
0.8 mm	PLC 4	
3.0 mm	PLC 4	
高电弧燃烧指数(HAI)		UL 746A
0.8 mm	PLC 0	
3.0 mm	PLC 0	
热性能	值	测试方法
RTI Elec		UL 746B
0.8 mm	65.0 °C	
3.0 mm	65.0 °C	
RTI Imp		UL 746B
0.8 mm	65.0 °C	
3.0 mm	65.0 °C	
RTI		UL 746B
0.8 mm	65.0 °C	
3.0 mm	65.0 °C	